



MEGA OIL X-2

Product Description:

Mega Oil X-2 Synthetic Engine Oil is a new passenger car motor oil (PCMO) that delivers the latest development of lubricating oil technology to maximize protection for the newest gasoline fueled engines. It meets the highest performance level of API SN and exceeds the most demanding requirements of modern engine's emission control and oil consumption standards. In today's energy conscious era, Mega Oil X-2 is also formulated to improve fuel efficiency for consumers.

Applications / Benefits:

- Exceeds the highest U.S Lubricating oils standards for gasoline and LPG/CNG engines.
- Silky smooth operation for all high performance engines.
- Increases emission system durability and improves fuel efficiency.
- Improves piston cleanliness and increases engine sludge protection.
- Increases wear protection and extends service life.

Typical Characteristics:

Test Description	Method	
SAE Viscosity Grade	SAE J 300	10W-40
Specific Gravity @ 15 °C	ASTM D 4052	0.871
Flash Point, °C	ASTM D 92	220
Pour Point, °C	ASTM D 97	-33
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	98.4
cSt @ 100°C	ASTM D 445	14.6
Viscosity Index	ASTM D 2270	155
TBN, mgKOH/g	ASTM D 2896	10.2
Color	ASTM D 1500	<3.5

Specifications, Approvals & Recommendations:

- API SN/CF
- ACEA A3/B3-12
- ACEA A3/B4-12
- MB 229.1 (v2012.2)
- MB 229.3 (v2012.2)
- VW 502.00 / 505.00
- PSA B71 2300
- Renault RN 700
- JASO MA2 (T903-2011)